

## Temperature Indicating Spray Nozzle

### Features

- Easy-to-read dial thermometer at rear of the nozzle provides accurate and continual monitoring of water temperature
- Plastic sight window
- Gauge assembly is recessed into the rubber cover for complete protection
- Alerts the operator to shut-down the steam valve upon cold water failure, preventing scalding and steam burn injuries ensuring operator safety
- Ensures a more accurate discharge water temperature reading
- 1/2" female NPT inlet
- Black cover

### Specifications

- Recommended for water temperatures to 200°F (93°C)
- Maximum operating pressure: 150 PSI
- 12.5 GPM flow capacity

**Bronze**  
**Part #**

BWSG-TI



## Stainless Steel Industrial Grade Spray Nozzle

### Application

- Recommended for use in corrosive applications where bronze and aluminum nozzles are not suitable

### Features

- Heavy duty 300-Series stainless steel body and barrel
- Variable spray pattern adjusts from a soft spray to a solid stream
- Replaceable rubber cover is specially formulated to resist a wide range of oils and chemicals and protect surrounding equipment
- 1/2" female NPT inlet

### Specifications

- Maximum operating pressure: 150 PSI
- Maximum flow: 12.5 GPM at 150 PSI
- Maximum temperature: 200°F (93°C)

**300 Stainless Steel**  
**Part #**

300SSSG



## Brass Industrial Grade Front Lever Spray Nozzle

### Features

- Provides effortless one hand operation; by actuating the operating lever the valve is opened/closed and the jet power is regulated from spray to concentrated jet
- Adjusting screw on back of gun allows you to fix the desired form of jet, fixing clamp for the operating lever allows lockable position for service
- 1/2" female NPT inlet
- Durable blue rubber cover

### Specifications

- Maximum operating pressure: 350 PSI
- Suitable for hot water up to 122°F (50°C)
- Flow: 6.6 GPM at 72 PSI

**Brass**  
**Part #**

DWG050

